

Safety Data Sheet

Date of issue: 12/02/2024 Revision date: 12/02/2024 Version: #2

SECTION 1: Identification

1.1. Identification

Product name : HIFISI 2223W10

Product form : Mixture

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Flow Improver, DRA, PPD, Hydrate Inhibitor

1.3. Supplier

FARSA Group Ltd

Sales@farsagroup.az

1.4. Emergency contacts

Emergency number : +994512707856

SECTION 2: Hazard(s) identification

Classification of the substance or mixture

 No carcinogenic effect has been observed. This product is not considered to be a hazardous substance or mixture when classified in accordance with Regulation 29 CFR 1910.1200 (US GHS)

No Mutagenic effect has been observed.

Classification according to Regulation:

- This product is not considered to be a hazardous substance or mixture when classified in accordance with Regulation 29 CFR 1910.1200 (US GHS).

No reproduction Toxicity effect has been observed.

Label elements Remarks:

- No labelling is required under Regulation 29 CFR 1910.1200 (US GHS).

Other hazards none known.

SECTION 3: Composition/information on ingredients

Component	CAS No.	Content
Acrylic copolymer	Trade secret	30-60%
Solvent	Proprietary	30-60%
Co-Solvent	Proprietary	5-10%
Dewaxed heavy paraffin	Proprietary	0.5-2%
Diesel	Proprietary	30-60%
Methanol	Proprietary	30-60%
Phosphoric Esther	Proprietary	1-3%

SECTION 4: First-aid measures

Ingestion

4.1. Description of first aid measures

General advice : The rescuer should always protect them from exposure prior to beginning rescue or first aid measures.

Inhalation : If inhaled, remove to fresh air. If symptoms persist, consult a physician for treatment.

Skin contact : Immediately wash skin with soap and plenty of water. Remove contaminated clothing. Obtain

medical attention immediately if symptoms occur. Wash clothing before reuse.

In case of contact, immediately flush eyes with plenty of water. Obtain medical attention if

Eye contact : In case of contact, immediately flush eyes with plenty of water. Obtain medical attention if irritation develops.

: If swallowed, only induce vomiting if directed by medical personnel. Get medical attention. Never give anything by mouth to an unconscious person.

Important symptoms and effects : Both acute and delayed Product has dermal fatting Effect. Indication of any immediate medical attention and special treatment needed.

12/02/2024 EN (English) 1/4

Safety Data Sheet

SECTION 5: Firefighting measures

Fire and explosion hazards

Extinguishing media Unsuitable extinguishing media

Special protective equipment for firefighters

Further information

- Combustible liquid and vapor. If heated above the flash point this product will release flammable vapors and burn vigorously. Mists and sprays may be flammable at temperatures below the flash point. Vapors are heavier than air and will flow along surfaces to remote ignition sources and flash back. Flammable vapors may collect in low areas.
- Use carbon dioxide (CO2), dry chemical, and foam or water fog.
- Do not use water jet as that may spread the fire.
- Fire fighters should wear appropriate protective equipment and self-contained breathing apparatus (SCBA) with a full face-piece operated in positive pressure mode. Prevent mixing with alkali and amines materials.
- Promptly isolate the scene by removing all persons from the vicinity of the incident if there is a fire. No action shall be taken

Involving a personal risk or without suitable training. Move containers from fire area if this can be done without risk. Use water spray to keep fire-exposed containers cool. Do not allow fire extinguishing water to contaminate surface or groundwater systems.

SECTION 6: Accidental release measures

Personal precautions Advice for non-emergency personnel

- Advice for emergency responders
- **Environmental precautions**
- Methods and materials for containment

- Clean up to spillage with cleaning cloths or absorbent paper, precaution is necessary.
- Evacuate the danger zone; follow emergency precautions. Secure emergency assistance immediately. Avoid contact with the material, do not breath dusts. If possible, provide
- Do not take action without proper training and emergency equipment. See Section 8 for additional information. Evacuate surrounding areas. Eliminate all ignition sources including flares and all open flames. Avoid all contact with spilled material. Maintain adequate ventilation and wear appropriate respiratory protection.
- Avoid dispersal of spilled material, runoff and contact with soil, waterways, drains and sewers. Inform the relevant authorities if the product has caused environmental pollution (sewers, waterways, soil or air). Avoid large quantities entering drains or water ways. Stop spill if without risk. Move containers from spill area. Approach release from upwind.
- Prevent entry into sewers, surface waters, basements or confined areas. Wash spillage into Prevent entry into sewers, surface waters, basements or confined areas. Wash spillage into effluent treatment plant. Contain and collect spillage using appropriate personal protective equipment. Chemical resistant, impervious gloves complying with an approved standard should be worn at all times when handing chemical products or if a risk assessment indicates this is necessary. Collect and contain spillage with non-combustible, absorbent material (e.g. sand, earth, vermiculite or diatomaceous earth) and place in a container for disposal according to local regulations. Use spark-proof tools and explosion proof equipment if flammable gasses, liquids or vapours are present in the spill area. Contaminated absorbent material may pose the same hazard(s) as the spilled product.

SECTION 7: Handling and storage

Precautions for safe handling

Observe all label precautions. Use appropriate personal protective equipment (see section 8). Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking. Do not get in eyes or on skin or clothing. Do not ingest.

Avoid breathing vapour or mist. Use only with adequate ventilation. Wear appropriate respirator when ventilation is inadequate. Do not enter storage areas and confined spaces unless adequately ventilated. Keep in the original container or an approved alternative made from a compatible material, kept tightly closed when not in use. Store and use away from heat, sparks, open flame or any other ignition source. To avoid fire or explosion, dissipate static electricity during transfer by grounding and bonding containers and equipment before transferring material.

Advice on protection against fire and explosion

Conditions for safe storage, including any incompatibilities

- Keep away from flames and sources of ignition including static.
- Store in accordance with local regulations. Store in a segregated and approved area. Store in original or bulk storage container protected from direct sunlight in a dry, cool and wellventilated area, away from incompatible materials (see section 10) and food and drink. Eliminate all ignition sources. Separate from oxidizing materials, amines and alkalis. Bulk storage should be in approved vessels, preferably steel that is grounded and vented Keep use containers tightly closed and sealed until ready for use. Containers that have been opened must be carefully resealed and kept upright to prevent leakage. Do not store in unlabeled containers. Use appropriate containment to avoid environmental contamination.

SECTION 8: Exposure controls/personal protection

Control parameters

Exposure controls

Personal, workplace or environmental monitoring may be necessary to ensure exposures are below recommended and legal limits.

Exposure limits

OSHA (US), Mexico, and EU have not developed specific exposure limits. Nuisance dust exposure limits are 100mg/m3 and 30 mg/m3 for respirable particles (8 hr TWA). Use recommended safe handling practices to minimize unnecessary exposure.

Exposure limits for chemicals which may be generated during processing

- During processing residual vinyl acetate may be released into the work environment. Maintain ventilation to ensure exposure limits are below 10 ppm TWA 8 hr and 15 ppm STEL 15 min (US); 5 ppm TWA and 10 ppm (EU). Vinyl acetate is classified as A3 carcinogen (animals).
- Engineering measures: Use only with adequate ventilation. Use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits. The engineering controls also need to keep gas, vapour or dust concentrations below any lower explosive limits.

12/02/2024 EN (English) 2/4

Safety Data Sheet

individual exposure measures	al exposure measures
------------------------------	----------------------

: Hygiene measures: Wash hands, forearms and face thoroughly after handling chemical products, before eating, smoking and using the lavatory and at the end of the working period. Appropriate techniques should be used to remove potentially contaminated clothing. Discard contaminated clothing or wash thoroughly before reusing. Ensure that eyewash stations and safety showers are close to the workstation location.

Eye/face protection

Safety eyewear complying with an approved standard should be used when a risk assessment indicates this is necessary to avoid exposure to product dusts, liquid splashes or mists. Goggles should be worn where eye contact is possible.

Hand protection

Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is required.

Glove material

Cotton or plastic (thermal resistant) Glove Thickness: 0.7 mm or thicker Break Through Time: > 240 minutes.

Other protective equipment

: Flame retardant antistatic protective clothing may be required if used in areas where flammables are processed.

Respiratory protection

: A properly fitted air purifying respirator or air supply respirator should be worn if a risk assessment indicates that respiratory protection is necessary. Respirator selection must be based upon known or measured levels of exposure.

Environmental exposure controls

Ventilation and engineering controls to protect workers and ventilate work area to at or below recommended employee exposure levels. Technical measures are preferred over use of personal protective equipment. Environmental controls, such as scrubber or thermal oxidizer may be required to prevent process releases to the atmosphere. Do not empty or flush into drains.

SECTION 9: Physical and chemical properties

Physical form	Liquid	OSHA Flammability Class	Not applicable
Colour	Pale yellow	LEL	Not applicable
Specific Gravity at 25°C	0.87 to 0.92 gm/cm3.	UEL	Not applicable
Flash point	> 60 °C (ASTM D 3278)	Auto ignition	Not applicable
Evaporation rate	No data available	Viscosity at 40 0C	20-150 cst.
Vapour density	Not applicable	-	-

SECTION 10: Stability and reactivity

: This material is considered stable under specified conditions of storage, shipment and/or

Reactivity

No hazardous reactivity.

Possibility of hazardous reactions

Product will not undergo polymerization at Processing Temperature.

Conditions to avoid

Avoid dust-air mixtures, static generation. Avoid contact with incompatible materials.

Incompatible materials

Thermal decomposition will yield oxides of carbon and/or acetic acid.

None when used as directed.

Hazardous decomposition products Under conditions of thermal decomposition

Methacrylate, when overheated.

SECTION 11: Toxicological information

Acute toxicity				
Acute oral toxicity LD50	Rat	Non toxic		
Acute dermal toxicity LD50	Rabbit	Non skin irritation		
Acute inhalation toxicity LC50	-	-		

Skin irritation Non irritating. Eye irritation (rabbit) No eye irritation. Sensitization No data available. Genotoxicity and reproductive effects No data available. STOT-single exposure No data available. STOT-repeated exposure No data available. Aspiration hazard No information available.

SECTION 12: Ecological information

Toxicity

No data available.

Persistence and degradability Bioaccumulative potential

No data available. Bioaccumulation not expired.

Mobility in soil Results of PBT and vPvB assessment No information available. Assessment not available.

Other adverse effects Additional ecological information No additional environmental adverse effects are known. Do not allow product to enter surface waters, wastewater or soil.

SECTION 13: Disposal considerations

Waste treatment methods

The generation of waste should be avoided or minimized wherever possible. Empty containers or liners may retain some product residues. This material and its container must

12/02/2024 EN (English)

Safety Data Sheet

be disposed of in a safe way. Dispose of surplus and non-recyclable products via a licensed waste disposal contractor. Disposal of this product, solutions and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements. Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

SECTION 14: Transport information

The transport regulations are cited according to international and/or harmonized transport regulations. Possible national deviations and country specific requirements are not considered.

US DOT information No classification assigned. **TDG** information No classification assigned. **ADR** information No classification assigned. **RID** information No classification assigned. No classification assigned. IATA information **ICAO** information No classification assigned. **IMDG** information No classification assigned.

SECTION 15: Regulatory information

US Federal regulations

This product is not listed under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 311/312 (40 CFR 370.21), SARA Section 313 (40 CFR 372.65), CERCLA (40 CFR 302.4), TSCA 12(b), or require an OSHA process safety plan. SARA Section 311/312 (40 CFR 370 Subparts B and C): Acute Health: no chronic health, no

fire, no pressure, no reactive:

US State regulations This product is not listed on the state lists from CA, MA, MN, NJ or PA. Not listed under

California Proposition 65. Note: residual vinyl acetate is a listed material.

Globally Harmonized System of This product has been checked for country-specific published classifications according to the classification and labelling (GHS) Globally Harmonized System of Classification and Labelling (GHS). European Union GHS Classifications : No published information available.

SECTION 16: Other information

No other information.

Disclaimer:

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

12/02/2024 EN (English)